




## P-Channel Enhancement Mode Field Effect Transistor



### Product Summary

- $V_{DS}$  -100V
- $I_D$  -20A
- $R_{DS(ON)}$  (at  $V_{GS}=-10V$ )  $<85m\Omega$
- $R_{DS(ON)}$  (at  $V_{GS}=-4.5V$ )  $<102m\Omega$
- 100% EAS Tested
- 100%  $\nabla V_{DS}$  Tested

### General Description

- Trench Power MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low  $R_{DS(ON)}$
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

### Applications

- Load switch
- Motor drive control
- DC-DC convertor

### Absolute Maximum Ratings ( $T_J=25^\circ C$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		$V_{DS}$	-100	V
Gate-source Voltage		$V_{GS}$	$\pm 20$	V
Continuous Drain Current (Note 1,2 )	Steady-State	$T_A=25^\circ C, V_{GS} = -10V$	-3.7	A
		$T_A=100^\circ C, V_{GS} = -10V$	-2.3	
Continuous Drain Current (Note 1,3 )	Steady-State	$T_C=25^\circ C, V_{GS} = -10V$	-20	
		$T_C = 100^\circ C, V_{GS} = -10V$	-12	
Pulsed Drain Current	$T_C=25^\circ C, t_p=100\mu s$	$I_{DM}$	-60	A
Avalanche energy	$V_G=-10V, R_G=25\Omega, L=0.5mH, IAS=-18A$	EAS	81	mJ
Total Power Dissipation (Note 1,2 )	Steady-State	$T_A=25^\circ C$	2.5	W
		$T_A=100^\circ C$	1	
Total Power Dissipation (Note 1,3 )	Steady-State	$T_C=25^\circ C$	89	
		$T_C = 100^\circ C$	35	
Junction and Storage Temperature Range		$T_J, T_{STG}$	-55~+150	°C

### Thermal resistance

Parameter		Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient (Note 2)	Steady-State	$R_{\theta JA}$	40	50	°C/W
Thermal Resistance Junction-to-Case	Steady-State	$R_{\theta JC}$	1.15	1.4	

### Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJD085P10A	F1/F2	YJD085P10A	2500	/	25000	13"Reel



# YJD085P10A

## ■ Electrical Characteristics ( $T_J=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
<b>Static Parameter</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=-250\mu\text{A}$	-100	-	-	V
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{\text{DS}}=-100\text{V}, V_{\text{GS}}=0\text{V}$	-	-	-1	$\mu\text{A}$
		$V_{\text{DS}}=-100\text{V}, V_{\text{GS}}=0\text{V}, T_J=150^\circ\text{C}$	-	-	-100	
Gate-Body Leakage Current	$I_{\text{GSS}}$	$V_{\text{GS}}=\pm20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	$\pm100$	nA
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=-250\mu\text{A}$	-1.5	-2	-2.5	V
Static Drain-Source On-Resistance	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=-10\text{V}, I_{\text{D}}=-10\text{A}$	-	70	85	$\text{m}\Omega$
		$V_{\text{GS}}=-4.5\text{V}, I_{\text{D}}=-5\text{A}$	-	75	102	
Diode Forward Voltage	$V_{\text{SD}}$	$I_{\text{S}}=-10\text{A}, V_{\text{GS}}=0\text{V}$	-	-	-1.2	V
Gate resistance	$R_{\text{G}}$	$f=1\text{MHz}$	-	10	-	$\Omega$
Maximum Body-Diode Continuous Current	$I_{\text{S}}$		-	-	-20	A
<b>Dynamic Parameters</b>						
Input Capacitance	$C_{\text{iss}}$	$V_{\text{DS}}=-50\text{V}, V_{\text{GS}}=0\text{V}, f=1\text{MHz}$	-	2070	-	$\text{pF}$
Output Capacitance	$C_{\text{oss}}$		-	90	-	
Reverse Transfer Capacitance	$C_{\text{rss}}$		-	70	-	
<b>Switching Parameters</b>						
Total Gate Charge	$Q_{\text{g}}$	$V_{\text{GS}}=-10\text{V}, V_{\text{DS}}=-50\text{V}, I_{\text{D}}=-10\text{A}$	-	44.4	-	$\text{nC}$
Gate-Source Charge	$Q_{\text{gs}}$		-	4.7	-	
Gate-Drain Charge	$Q_{\text{gd}}$		-	5.5	-	
Reverse Recovery Charge	$Q_{\text{rr}}$	$I_{\text{F}}=-10\text{A}, \text{di/dt}=100\text{A/us}$	-	45	-	$\text{nC}$
Reverse Recovery Time	$t_{\text{rr}}$		-	30	-	ns
Turn-on Delay Time	$t_{\text{D(on)}}$	$V_{\text{GS}}=-10\text{V}, V_{\text{DD}}=-50\text{V}, I_{\text{D}}=-10\text{A}$ $R_{\text{GEN}}=3\Omega$	-	9	-	ns
Turn-on Rise Time	$t_{\text{r}}$		-	42	-	
Turn-off Delay Time	$t_{\text{D(off)}}$		-	91	-	
Turn-off fall Time	$t_{\text{f}}$		-	31	-	

Note:

- The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
- The value of  $R_{\text{thJA}}$  is measured with the device mounted on the 40mm\*40mm\*1.1mm single layer FR-4 PCB board with 1 in<sup>2</sup> pad of 2oz. Copper, in the still air environment with TA =25°C. The maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- Thermal resistance from junction to soldering point (on the exposed drain pad).



**YJD085P10A**

■ Typical Electrical and Thermal Characteristics Diagrams




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. On-Resistance vs Gate to Source Voltage




Figure 6. Normalized On-Resistance



**YJD085P10A**




Figure 7. RDS(on) VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation



YJD085P10A




Figure 13. Maximum Transient Thermal Impedance





Figure 14. Safe Operation Area



## ■ TO-252-B Package information



SYMBOL	DIMENSIONS			Millimeter		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A1	0.000	---	0.008	0.000	---	0.200
A2	0.087	0.091	0.094	2.200	2.300	2.400
A3	0.035	0.039	0.043	0.900	1.000	1.100
b	0.026	0.030	0.034	0.660	0.760	0.860
c	0.018	0.020	0.023	0.460	0.520	0.580
D	0.256	0.260	0.264	6.500	6.600	6.700
D1	0.203	0.209	0.215	5.150	5.300	5.450
D2	0.181	0.189	0.195	4.600	4.800	4.950
E	0.390	0.398	0.406	9.900	10.100	10.300
E1	0.236	0.240	0.244	6.000	6.100	6.200
E2	0.203	0.209	0.215	5.150	5.300	5.450
e	0.090BSC			2.286BSC		
L	0.049	0.059	0.069	1.250	1.500	1.750
L1	0.035	---	0.050	0.900	---	1.270
L2	0.055	---	0.075	1.400	---	1.900
L3	0.024	0.031	0.039	0.600	0.800	1.000
L4	0.114REF			2.900REF		
θ	0°	---	10°	0°	---	10°

## NOTE:

- 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
- 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
- 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use or sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.