


Silicon Carbide Power MOSFET (N-Channel Enhancement)

V _{DS}	1200V
I _{D (25°C)}	39A
R _{DS(on)}	80mΩ



Features

- High speed switching
- Essentially no switching losses
- Reduction of heat sink requirements
- Maximum working temperature at 175 °C
- High blocking voltage
- Fast Intrinsic diode with low recovery current
- High-frequency operation
- Halogen free, RoHS compliant

Typical Applications

Typical applications are in power factor correction(PFC), solar inverter, uninterruptible power supply, motor drives, photovoltaic inverter, electric car and charger.

Mechanical Data

- **Package:** TO247-4L
- **Terminals:** Tin plated leads
- **Polarity:** As marked

■Maximum Ratings (T_C=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE	TEST CONDITIONS	NOTE
Device marking code				D212080NCFG1	
Drain source voltage @ T _j =25°C	V _{DS,max}	V	1200	V _{GS} =0 V, I _D =100uA	
Gate source voltage @ T _j =25°C	V _{GS,max}	V	-8/+22	Absolute maximum values	Note1
Gate source voltage @ T _j =25°C	V _{GS,op}	V	-4/+18	Recommended operational values	Note2
Continuous drain current @ T _c =25°C	I _D	A	39	V _{GS} =18V, T _c =25°C	Fig.18
Continuous drain current @ T _c =100°C			28	V _{GS} =18V, T _c =100°C	
Pulsed drain current	I _{D(pulsed)}	A	80	Pulse width t _p limited by T _{j,max}	Fig.23
Power Dissipation	P _{TOT}	W	214	T _c =25°C , T _j = 175°C	Fig.17
Operating junction and Storage temperature range	T _j , T _{stg}	°C	-55 to +175		
Soldering temperature	T _L	°C	260	1.6mm (0.063") from case for 10s	
Mounting torque	T _M	Nm	0.6	M3 screw Maximum of mounting process: 3	



■ Static Electrical Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Gate threshold voltage	V _{GS(th)}	V	2.3	2.9	3.6	V _{DS} =V _{GS} , I _D = 5mA	Fig.4, 11
				2.2		V _{DS} =V _{GS} , I _D = 5mA, Tj=175°C	
Drain source breakdown voltage	V _{(BR)DSS}	V	1200			V _{GS} =0, I _D =100uA	
Zero gate voltage drain current	I _{DSS}	uA		1	10	V _{DS} =1200V, V _{GS} = 0V	Fig.16
Gate source leakage current	I _{GSS}	nA			100	V _{GS} = 18V, V _{DS} =0V	
Current drain source on-state resistance	R _{DS ON}	mΩ		77	85	V _{GS} =18V, I _D =20A	Fig.5, 6, 7
				122		V _{GS} =18V, I _D =20A, Tj=175°C	
Internal gate resistance	R _g	Ω		3.1		f=1MHz	
Diode forward voltage	V _{SD}	V		3.9		V _{GS} =-4V, I _{SD} =10A	Fig.8
				3.2		V _{GS} =0V, I _{SD} =10A Tj=175°C	Fig.9
Transconductance	g _f	S		10		V _{DS} =16V, I _D =20A	Fig.4
				9.2		V _{DS} =16V, I _D =20A, Tj=175°C	

■ Dynamic Electrical Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Input capacitance	C _{iss}	pF		890		V _{DS} =1000V, V _{GS} =0V, Tj=25°C, f=1MHz, V _{AC} = 25mV	Fig.13, 14
Output capacitance	C _{oss}			58			
Reverse capacitance	C _{rss}			4			
C _{oss} stored energy	E _{oss}	uJ		34		V _{DS} =800V, V _{GS} =-4/18V, I _D =20A	Fig.15
Gate source charge	Q _{gs}	nC		12			Fig.12
Gate drain charge	Q _{gd}			11			
Gate charge	Q _g			41			



■Switching Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Turn on switching energy	E _{on}	uJ		112		V _{DD} =800V, V _{GS} =-4/+18V, I _D =20A, R _g =0Ω, L=120uH	Fig.21, 22
Turn off switching energy	E _{off}			25			
Turn on delay time	t _{d(on)}	ns		8.8		V _{DD} =800V, V _{GS} =-4/+18V, I _D =20A, R _g =0Ω, L=220uH	Fig.21, 22
Rise time	t _r			10.5			
Turn off delay time	t _{d(off)}	ns		15		V _{DD} =800V, V _{GS} =-4/+18V, I _D =20A, R _g =0Ω, L=220uH	Fig.21, 22
Fall time	t _f			8.4			

■Body diode characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Diode forward voltage	V _{SD}	V		3.9		V _{GS} =-4V, I _{SD} =10A	Fig.8
				3.2		V _{GS} =0V, I _{SD} =10A, T _j =175°C	Fig.9
Continuous diode forward current	I _s	A		39		Tc=25°C	Note1
Reverse recovery time	trr	nS		41		V _R =800V, V _{GS} =-4V, I _D =20A, dI/dt=700A/uS	
Reverse recovery charge	Qrr	nC		405			
Peak reverse recovery current	Irrm	A		20			

Note 1: When using SiC Body Diode the maximum recommended V_{GS} = -4V

Note 2: MOSFET can also safely operate at 0/18 V

■Thermal Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Value
Thermal resistance	R _{θJ-C}	°C/W	0.7

■ Typical Characteristics




Figure 1. Output Characteristics $T_j = -40^\circ\text{C}$




Figure 2. Output Characteristics $T_j = 25^\circ\text{C}$




Figure 3. Output Characteristics $T_j = 175^\circ\text{C}$




Figure 4. Transfer Characteristics for various junction temperature




Figure 5. On-resistance vs. temperature for various gate voltage




Figure 6. Normalized on-resistance vs. temperature




Figure 7. On-resistance vs. drain current




Figure 8. Body diode characteristic at $T_j = 25 \text{ }^{\circ}\text{C}$




Figure 9. Body diode characteristic




Figure 10. 3rd quadrant characteristic at $T_j = 25 \text{ }^{\circ}\text{C}$




Figure 11. Threshold voltage vs. temperature




Figure 12. Gate charge characteristic




Figure 13. Capacitances vs.drain source voltage (0-1000V)




Figure 14. Capacitances vs.drain source voltage (0-200V)




Figure 15. Output capacitor stored energy




Figure 16. Reverse characteristics vs. T_j




Figure 17. Maximum power dissipation derating vs. case temperatere




Figure 18. Continuous drain current derating vs. case temperatere




Figure 19. Transient thermal impedance (junction - case)




Figure 20. Clamped Inductive switching energy vs. drain current




Figure 21. Switching times vs. R_g




Figure 22. Safe operating area




Figure 23. Switching Times Definition





Figure 24. Clamped Inductive Switching Waveform Test Circuit

■Outline Dimensions



TO247-4L			
Dim	Min	Norm	Max
A	4.80	5.00	5.20
A1	2.30	2.40	2.50
A2	1.88	1.98	2.08
b	1.10	1.20	1.30
b1	1.20	/	1.50
b2	2.35	2.55	2.75
b3	2.45	/	2.85
c	0.55	0.60	0.65
D	23.3	23.45	23.6
D1	16.25	16.55	16.85
D2	1.00	/	1.30
e	TYP2.54		
e1	TYP5.06		
E	15.75	15.90	16.05
E1	13.80	/	14.20
E2	4.40	4.75	5.10
E3	13.00	/	13.45
L	17.34	17.49	17.64
L1	4.00	/	4.30
L2	2.35	/	2.65
L3	TYP1.98		
Q	5.60	5.80	6.00
S	6.05	/	6.30
p	TYP3.58		
p1	TYP7.18		
p2	TYP3.00		



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.