


PNP General Purpose Amplifier

SOT-223



1-Base
2-Collector
3-Emitter
4-Collector

Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture sensitivity level 1
- Low collector-emitter saturation voltage


Mechanical Data

- **Package:** SOT-223
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:**

DPLS4140Z

P4140Z

■Equivalent circuit



■Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Minimum Collector-Emitter Voltage	V_{CEO}	V	$I_C = -10\text{mA}$, $I_B = 0$	-140
Minimum Collector-Base Voltage	V_{CBO}	V	$I_C = -100\mu\text{A}$, $I_E = 0$	-180
Minimum Emitter-Base Voltage	V_{EBO}	V	$I_E = -100\mu\text{A}$, $I_C = 0$	-7
Collector Current	I_C	A		-4
Collector Power Dissipation	P_C	mW		500
Operation Junction Temperature	T_j	°C		-55 to +150
Storage Temperature	T_{stg}	°C		-55 to +150

**■Electrical Characteristics** (Ta=25℃ unless otherwise noted)


Item	Symbol	Unit	Conditions	Min	TYP	Max
Collector-Emitter Voltage	V_{CEO}	V	$I_C=-10mA, I_B=0$	-140		
Collector-Base Voltage	V_{CBO}	V	$I_C=-100\mu A, I_E=0$	-180		
Emitter-Base Voltage	V_{EBO}	V	$I_E=-100\mu A, I_C=0$	-7		
Collector-Base cut-off current	I_{CBO}	μA	$V_{CB}=-150V$			-0.1
Emitter-Base cut-off current	I_{EBO}	μA	$V_{EB}=-6V$			-0.1
DC Current Gain	h_{FE1}		$V_{CE}=-5V, I_C=-10mA$	100		
	h_{FE2}		$V_{CE}=-5V, I_C=-1A$	100		300
	h_{FE3}		$V_{CE}=-5V, I_C=-3A$	45		
Collector-Emitter Saturation Voltage	$V_{CE(sat)1}$	mV	$I_C=-0.1A, I_B=-5mA$			-60
	$V_{CE(sat)2}$	mV	$I_C=-0.5A, I_B=-50mA$			-120
	$V_{CE(sat)3}$	mV	$I_C=-1A, I_B=-100mA$			-150
	$V_{CE(sat)4}$	mV	$I_C=-3A, I_B=-300mA$			-360
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	V	$I_C=-3A, I_B=-300mA$	-	-	-1.04
Base-Emitter Turn-On Voltage	$V_{BE(on)}$	V	$V_{CE}=-5V, I_C=-3A$	-	-	-0.93
Output Capacitance	C_{ob}	pF	$V_{CB}=-10V, I_E=0, f=1MHz$		45	

■Ordering Information (Example)



PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
DPLS4140Z	F2	Approximate 0.11	2500	5000	25000	13" reel



■ Characteristics (Typical)




■SOT-223 Package Outline Dimensions



DIM	DIMENSIONS			
	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.0591	0.0670	1.5000	1.7000
A1	0.0008	0.0039	0.0200	0.1000
b	0.0259	0.0330	0.6600	0.8400
b1	0.1140	0.1220	2.9000	3.1000
c	0.0090	0.0138	0.2300	0.3500
D	0.2480	0.2640	6.3000	6.7000
E	0.2637	0.2874	6.7000	7.3000
E1	0.1290	0.1460	3.3000	3.7000
e	0.0866	0.0945	2.2000	2.4000
L	0.0295	0.0492	0.7500	1.2500
θ	0°	10°	0°	10°

■SOT-223 Suggested Pad Layout





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.