


General Purpose Rectifier



Features

- Glass passivated chip junction
- High surge forward current capability
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package:** TO-263
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked

■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GPB1010
Device Marking Code			GPB1010
Maximum Repetitive peak reverse voltage	V_{RRM}	V	1000
Maximum RMS Voltage	V_{RMS}	V	700
Maximum DC Blocking Voltage	V_{DC}	V	1000
Average Rectified Output Current @60Hz half sine-wave, R-load, Tc(FIG.1)	I_o	A	10
Surge(Non-repetitive) Forward Current @60Hz half sine-wave, 1 cycle, Ta=25°C	IFSM	A	200
Current Squared Time @1ms≤t<8.3ms Ta=25°C	I ² t	A ² s	166
Typical junction capacitance @ 1 MHz and Applied Reverse Voltage of 4.0V D.C.	Cj	pF	50
Storage Temperature	Tstg	°C	-55 ~ +150
Junction Temperature	Tj	°C	-55 ~ +150

■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	GPB1010
Maximum instantaneous forward voltage drop per diode	VFM	V	IFM=10.0A	1.1
Maximum DC reverse current at rated DC blocking voltage per diode	IRRM1	μA	VRM=VRRM Ta=25°C	5
	IRRM2		VRM=VRRM Ta=125°C	100



GPB1010





■ Thermal Characteristics ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	GPB1010
Typical Thermal Resistance	Between junction and case	$R_{\theta J-C}$	$^{\circ}\text{C/W}$	3.0

■ Ordering Information (Example)


PREFERED P/N	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GPB1010	Approximate 1.48	50	1000	5000	Tube

■ Characteristics (Typical)





■Outline Dimensions



TO-263		
Dim	Min	Max
A	9.5	11.5
B	9.7	10.5
C	8.4	9.0
D	0.28	0.64
E	0.68	0.94
F	4.55	5.6
G	4.04	5.10
H	1.14	1.4
I	0	0.2
J	4.9	6.05
K	1.79	2.79
L	7.3	7.9
M	6.2	6.8
N	7.6	8.2



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.